

HDBaseT Output Card 500476

Overview

The HDBaseT Output Card (500476) is a 4-channel module for MuxLab's Multimedia 16x16 Matrix Switch. The card provides extended distance via Cat5e/6 cable for to four ports and works in conjunction with the HDMI Receiver (500451-RX).



Applications

Digital signage, retail, residential, boardroom projector systems, classroom training, professional video editing, medical imaging, courtroom systems, rental and staging, video kiosks, airport video information systems, emergency operations centers, multimedia entertainment centers.

Key Features

4-channel HDBaseT Output Card
Hot-swappable

Specifications – HDBaseT Output Card (500476)	
Environment	HDBaseT
Devices	HDBaseT Extender Receiver
Transmission	Transparent to the user
Connectivity	4-port RJ45 connector
Maximum Distance	UTP/STP Cat 5e/6 Output port: 230 feet (70 meters)
Cables	Cat 5e/6 UTP/STP cables (or better)
LED Diagnostics	Link (Blue)
Compatible Receiver	HDMI Econo Mono Receiver for HDBaseT (500451-RX)
Temperature	Operating: 0°C to 50°C Storage: -20°C to 85°C Humidity: Up to 95% non-condensing
Dimensions	160 x 150 x 25 mm
Weight	0.55 lb (0.23 kg)
Regulatory	FCC, CE, RoHS, WEEE
Warranty	Two (2) years
Order Information	500476 4 Channel HDBaseT Output Card 500451-RX HDMI Econo Mono Receiver (HDBaseT/70m). Please refer to the 500451 datasheet for more information.