

Overview:

The AV over IP 4K/60 Uncompressed Extender, UTP allows HDMI source equipment supporting up to 4K @ 60Hz resolution to be connected and extended to create a 4K/60 HDMI based Video Wall, Virtual Matrix Switch, and Virtual Splitter arrangements of user configurable size (X by Y) supporting 100's of screens, depending on network bandwidth, utilizing one Receiver for each display in the array. Each Transmitter (500760-TX) and Receiver (500760-RX) can be connected via Cat5e/6 cable up to 330ft (100m) from a 10Gig Ethernet Switch.



The units come with a power supply, an IR Sensor (for TX) and an IR Emitter (for RX) for IR based remote control applications, and a wall mount bracket kit for securing the unit to a wall.

The MuxLab Pro Digital Network Controller is available to simplify centralized configuration and control, software updates and allows for connectivity management from MuxControl and other third party applications running on smartphones and tablets.

Key Features:

- Supports HDMI up to 4K/60 on Transmitter and Receiver
- Uncompressed up to 4K/60 (4:2:0), and light compression visually lossless at (4:4:4) (with zero latency)
- Supports Video Wall, Virtual Switch & Splitter configurations
- Supports point-to-point, point-to-multipoint and multipoint-to-multipoint applications
- Transmission up to 330ft (100m) over Cat5e/6
- 1G Ethernet Switch port to connect network devices
- Supports RS232 and IR transmission for remote control
- Managed via Pro Digital Network Controller, MuxControl Smartphone & Tablet App, and third party Apps

Specifications																			
Environment	HDMI 2.0																		
Devices	Blu-Ray, projectors, monitors, TV, PC, laptops, and media servers supporting HDMI.																		
Bandwidth	594MHz																		
Signals	HDMI 2.0 and HDCP 2.2																		
Connectors	Connectors per TX and RX: One (1) HDMI receptacle. Two (2) RJ45S for Cat 5e/6 unshielded or shielded twisted pair (for 10GbE and 1GbE ports). Two (2) 3.5mm jacks for IR emitter and IR sensor. One (1) DB9 connector for RS232. One (1) 2.1mm power jack (for DC power).																		
<i>Note: Cables not included.</i>																			
Maximum Distance	Cat5e/6: 330ft (100m) up to 4K @ 60Hz <i>Note: When installed in an electrically noisy environment, an STP cable must be used. Also, cross-connection reduces the effective distance depending on the grade of twisted cable used.</i>																		
<i>Based on a maximum length of 6.6ft (2m) of HDMI cable per end.</i>																			
Latency	Zero latency (undetectable in human terms)																		
Compression	Uncompressed up to 4K/60 (4:2:0), and light compression for 4K/60 (4:4:4) only																		
Network Bandwidth	< 10Gbps																		
Network Requirement	10Gig Network XFI, IEEE 802.3																		
IR Frequency	38 to 56KHz																		
RJ45 Pin Configuration	<p>RJ45 Link</p> <table border="0"> <tr> <td>Pin 1 (R)</td> <td>Pin 2 (T)</td> </tr> <tr> <td>Pin 3 (R)</td> <td>Pin 6 (T)</td> </tr> <tr> <td>Pin 4 (R)</td> <td>Pin 5 (T)</td> </tr> <tr> <td>Pin 7 (R)</td> <td>Pin 8 (T)</td> </tr> </table> <p><i>Reverse Polarity Sensitive. Use EIA/TIA 568A or 568B straight-through wiring.</i></p>	Pin 1 (R)	Pin 2 (T)	Pin 3 (R)	Pin 6 (T)	Pin 4 (R)	Pin 5 (T)	Pin 7 (R)	Pin 8 (T)										
Pin 1 (R)	Pin 2 (T)																		
Pin 3 (R)	Pin 6 (T)																		
Pin 4 (R)	Pin 5 (T)																		
Pin 7 (R)	Pin 8 (T)																		
Cable	One (1) Cat 5e/6 or better twisted pair cables required																		
Power Source	Input: 100-240V/1.5A (max) @ 50-60Hz Output: 5DC @ 4A Includes appropriate power cord for region (US, UK or Euro)																		
Power Consumption	Transmitter: 16 Watts Receiver: 16 Watts																		
Temperature	Operating: 0° to 40°C Storage: -20° to 85°C Humidity: Up to 95% non-condensing																		
Dimensions	6.3" x 4.8" x 1.0" (160mm x 122mm x 25mm)																		
Weight	1.38lbs (0.63kg)																		
Compliance	Regulatory: FCC, CE, RoHS Flammability: 94V0																		
Warranty	3 years																		
Order Information	<table border="0"> <tr> <td>500760-TX-US</td> <td>AV over IP 4K/60 Uncompressed Transmitter, UTP, US</td> <td>(UPC: 627699907603)</td> </tr> <tr> <td>500760-RX-US</td> <td>AV over IP 4K/60 Uncompressed Receiver, UTP, US</td> <td>(UPC: 627699807606)</td> </tr> <tr> <td>500760-TX-UK</td> <td>AV over IP 4K/60 Uncompressed Transmitter, UTP, UK</td> <td>(UPC: 627699917602)</td> </tr> <tr> <td>500760-RX-UK</td> <td>AV over IP 4K/60 Uncompressed Receiver, UTP, UK</td> <td>(UPC: 627699817605)</td> </tr> <tr> <td>500760-TX-EU</td> <td>AV over IP 4K/60 Uncompressed Transmitter, UTP, EU</td> <td>(UPC: 627699927601)</td> </tr> <tr> <td>500760-RX-EU</td> <td>AV over IP 4K/60 Uncompressed Receiver, UTP, EU</td> <td>(UPC: 627699827604)</td> </tr> </table>	500760-TX-US	AV over IP 4K/60 Uncompressed Transmitter, UTP, US	(UPC: 627699907603)	500760-RX-US	AV over IP 4K/60 Uncompressed Receiver, UTP, US	(UPC: 627699807606)	500760-TX-UK	AV over IP 4K/60 Uncompressed Transmitter, UTP, UK	(UPC: 627699917602)	500760-RX-UK	AV over IP 4K/60 Uncompressed Receiver, UTP, UK	(UPC: 627699817605)	500760-TX-EU	AV over IP 4K/60 Uncompressed Transmitter, UTP, EU	(UPC: 627699927601)	500760-RX-EU	AV over IP 4K/60 Uncompressed Receiver, UTP, EU	(UPC: 627699827604)
500760-TX-US	AV over IP 4K/60 Uncompressed Transmitter, UTP, US	(UPC: 627699907603)																	
500760-RX-US	AV over IP 4K/60 Uncompressed Receiver, UTP, US	(UPC: 627699807606)																	
500760-TX-UK	AV over IP 4K/60 Uncompressed Transmitter, UTP, UK	(UPC: 627699917602)																	
500760-RX-UK	AV over IP 4K/60 Uncompressed Receiver, UTP, UK	(UPC: 627699817605)																	
500760-TX-EU	AV over IP 4K/60 Uncompressed Transmitter, UTP, EU	(UPC: 627699927601)																	
500760-RX-EU	AV over IP 4K/60 Uncompressed Receiver, UTP, EU	(UPC: 627699827604)																	

Typical Application

