

Overview:

The HDMI 4K/ST2110 over IP Uncompressed Gateway Converter allows lower cost HDMI 4K equipment to be utilized in a broadcast environment and extended up to 1300ft (400m) via duplex multimode OM4 fiber with LC connectors, at up to 4K resolution @ 30Hz uncompressed, in a point-to-point configuration. Point-to-multipoint and multipoint-to-multipoint configurations are also possible by connecting several units to a 10G Ethernet network. The unit provides a 1G Ethernet Switch port to connect additional network devices, and an RS232 port for remote control of end devices.

The HDMI 4K/ST2110 over IP Uncompressed Gateway Converter supports SMPTE ST-2110 and a Rest API for third party management.

Applications:

- Commercial broadcast AV systems
- News/sports/TV stations
- Movie networks.



Key Features:

- Supports Uncompressed HDMI video up to 4K @ 30Hz and SMPTE ST-2110
- Extend HDMI over an IP network at up to 1300ft (400m) over duplex OM4 fiber
- Supports 100's of Transmitters & Receivers depending on network bandwidth
- Supports point-to-point, point-to-multipoint and multipoint-to-multipoint applications
- Supports two 10G Ethernet ports for communications and a 1G Switch port for additional network devices
- Supports audio insert (TX) & audio extract (RX)
- Supports RS232 for remote control of end devices
- Manage with third party control software platforms supporting a Rest API

| | |
|---|---|
| Environment | HDMI |
| Devices | Cameras, mixers, media players, monitors, TV, PC, laptops, servers supporting HDMI. |
| Signals | Up to HDMI 1.4 |
| Connectors/Switches | One (1) HDMI connector Two (2) SFP Connectors for 10G Ethernet Switch ports One (1) RJ45S Connector for 1G Ethernet Switch port One (1) 3-position Phoenix Connector for RS232 One (1) 3.5mm audio connector One (1) 2.1mm locking power connector |
| Max Distance | OM4: 1300ft (400m), OM3: 985ft (300m) |
| Latency | Zero latency |
| Compression | None (uncompressed) |
| Network Bandwidth | Up to 10 Gbps |
| Network Requirement | 10G Ethernet LAN |
| Cable | Two (2) Dual multi-mode fiber cables |
| Power Consumption | 15 Watt |
| Temperature | Operating: 0° to 40°C Storage: -20° to 85°C Humidity: Up to 95% non-condensing |
| Enclosure | Aluminium |
| Dimensions | 4.4" x 7" x 1.0" (11.1 x 17.5 x 2.5 cm) |
| Weight | 1.5 lb (0.7 kg) |
| Compliance | Regulatory: FCC, CE, RoHS Flammability: 94V0 |
| Warranty | 3 years |
| Order Information | 500774-TX-MM: HDMI 4K/ST2110 over IP Uncompressed Transmitter, MM fiber (UPC: 627699917749) 500774-RX-MM: HDMI 4K/ST2110 over IP Uncompressed Receiver, MM fiber (UPC: 627699817742) |
| Accessories (Sold separately) | 500920 16-Port Rackmount Transceiver Chassis 500917 Wall Mount Transceiver Bracket Kit |

Typical Application

