

DigiSign MXC

Quick Installation Guide

500799-1080P



Table of Contents

1. Safety Precautions.....	3
2. Introduction.....	4
3. Features.....	4
4. Applications.....	4
5. Specifications.....	5
6. Installation.....	6
7. Troubleshooting.....	7

1. Safety Precautions

To ensure the best performance from the product, please read all instructions carefully before using the device. Save this manual for future reference.

- Follow basic safety precautions to reduce the risk of fire, electrical shock, and injury.
- Do not dismantle the housing or modify the module. It may result in electrical shock or burns.
- Do not open or remove the housing of the device as you may be exposed to dangerous voltage or other hazards.
- To prevent fire or shock hazard, do not expose the unit to rain, moisture and do not install this product near water. Keep the product away from liquids.
- Spillage into the housing may result in fire, electrical shock, or equipment damage. If an object or liquid falls or spills on the housing, unplug the module immediately.
- Do not use liquid or aerosol cleaners to clean this unit. Always unplug the power to the device before cleaning.
- Using supplies or parts not meeting the product specifications may cause damage, deterioration or malfunction.
- Refer all servicing to qualified service personnel.
- Install the device in a place with adequate ventilation to avoid damage caused by overheating.
- Unplug the power when left unused for a long period of time.
- Information on disposal of devices: do not burn or mix with general household waste, please treat them as normal electrical waste.

Copyright Notice

All contents in this manual are copyrighted, and cannot be cloned, copied, or translated without the express permission of MuxLab Inc. Product specifications and information in this document are for reference only, and the content may be updated from time to time without prior notice.

2. Introduction

The DigiSign MXC (model 500799-1080P) is capable of playing multiple audio/video signage content simultaneously in a multiview window up to 1080p at 60Hz from a local network, the Internet, or player internal memory, and supports multiview capability including multiple 1080p videos and supports a scheduler to automatically deliver the windowed audio/video content based on a yearly schedule. Multiple video, audio and image file formats are supported. The unit delivers 1080p at 60Hz content to a display or to a MuxLab AV over IP system to be distributed to multiple displays and video wall arrangements. The Player supports a Keyword Dictionary and Interactive Mode.

The DigiSign MXC is managed by the DigiSign CMS (Content Management System) Software running on a PC, which supports video, audio and image content as well as HTML5, RSS feeds and many other widgets. DigiSign CMS can easily and quickly create digital signage content and schedule the content to be played on the Player.

3. Features


- Supports up to 1080p at 60Hz video streams
- Decodes H.264/265 video streams over the Internet and local network
- Multi-format video, image and audio files
- Plays slides & playlists on a flexible, intuitive yearly scheduler
- 1 x USB 3.0, 2 x USB 2.0
- Multi-view & PiP layouts
- Display rotation capability
- Touch gestures such as tap and swipe for interactive experiences
- Remote preview of player output
- Supports PoE or 5VDC power supply

4. Applications

Applications include digital signage / media player, audio/video streaming over LAN and Internet, commercial and residential AV systems, corporate lobbies, malls and boutiques, airports, subway/train/bus stations, etc.

5. Specifications

Technical	
Environment	HDMI 1.4
Devices	TVs, monitors, projectors supporting HDMI.
Signal Protocol/Standard	HDMI 1.4 and HDCP 1.3
Video Bandwidth	297MHz
Network Bandwidth	25Mbps (typical)
Protocols	Supports Multicast & HLS
Connectors	One (1) HDMI output connectors for AV. One (1) RJ45 Ethernet connection for LAN connection. One (1) USB 3.0 connector (for future use). Two (2) USB 2.0 connector (for future use). One (1) MicroSD connector (for future use) One (1) OTG connector One (1) 3.5mm output connector for audio extraction. One (1) SPDIF output connector for audio extraction. One (1) 2.1mm power connector.
Maximum Distance	Cat5e/6: 330ft (100m) from Ethernet Switch. Unlimited over the Internet Note: When installed in an electrically noisy environment, an STP cable must be used. Also, cross-connection reduces the effective distance depending on the grade of twisted cable used.
RJ45 Pin Configuration	RJ45 Link Pin 1 (R) Pin 2 (T) Pin 3 (R) Pin 6 (T) Pin 4 (R) Pin 5 (T) Pin 7 (R) Pin 8 (T)
Power Supply	Includes a 5VDC/ 2.5A power adapter.
Power Consumption	12W
Temperature	Operating: 0° to 40°C Storage: -20° to 85°C Humidity: Up to 95% non-condensing
Dimensions	3.9" x 3.8" x 0.9" (99mm x 97mm x 24mm)
Weight	0.48 lbs (0.21kg)
Compliance	Regulatory: FCC, CE, RoHS Flammability: 94V0
Warranty	3 years
Order Information	500799-1080P DigiSign MXC (UPC: 627699027998)




6. Installation

1. Connect the player to the HDMI display equipment with an HDMI compliant cable, or alternatively connect the Player to an AV over IP Transmitter to be able to connect to multiple AV over IP Receivers and/or video walls and turn on the Display equipment.
2. Using a CAT5/6 cable connect the Ethernet port of the player to an Ethernet switch.
3. Next connect the power supply to the unit and then to an AC outlet. The Power LED will turn on and the unit will start up.
4. MuxLab's DigiSign CMS software can now be used to discover the 500799-1080P and manage the unit. Please reference the DigiSign manual on how to discover, manage and publish Signage content to this unit.

The unit is configured in DHCP mode by default, and will be assigned an IP address if your network has a DHCP server.

5. If audio extraction is required, connect a Stereo 3.5 mm audio cable to the 3.5 mm jack for analog audio, or a Digital Optical audio cable to the SPDIF connector and then connect the other cable end to audio equipment.
6. The following diagram illustrates a typical configuration.



7. Troubleshooting

The following table describes some of the symptoms, probable causes and possible solutions in regard to the installation of the DigiSign Android Signage Player:

Symptom	Probable Cause	Possible Solutions
No Power LED	No power to the unit	• Check power connections
Choppy Video	Configuration	• Check cable length • Check the HDMI Cable Quality • Check if IGMP is enabled on the Ethernet Switch • Validate your video stream
USB drive not detected	(function not available in current release, for future use)	(function not available in current release, for future use)

If you still cannot diagnose the problem, please call MuxLab Customer Technical Support at 877-689-5228 (toll-free in North America) or (+1) 514-905-0588 (International).