



HDMI over IP PoE Wall-Plate Seamless Transceiver, 4K30

500865-WP-WH



Overview

The HDMI over IP PoE Wall-Plate Seamless Transceiver, 4K/30 (model: 500865-WP-WH) allows HDMI source equipment to be extended locally up to 330ft (100m) at up to 4K @ 30Hz resolution via Cat5e/6 cable and is compatible with the MuxLab 500860 and 500861 Transceivers to support point-to-point, point-to-multipoint and multipoint-to-multipoint configurations, Video Wall and Multiview capabilities in a low bandwidth expandable and cost effective manner, without the need to install dedicated cabling systems. The exceptionally low bandwidth requirements of this device combination allows for streaming audio/video content over a local network, over WiFi, and over the Internet for distributed installations spread throughout the globe. The Transceiver accepts a 4K video @ 30Hz and streams the content to an H.264/H.265 Receiver to be displayed on a 4K monitor. The device supports PoE (PD) and may be powered by a PoE (PSE) Ethernet Switch.

Applications

- Audio/Video Streaming over LAN, Wifi and Internet
- Commercial and residential AV systems
- Classroom projector systems
- Digital signage
- Boardroom systems
- Medical information systems

Key Features

- Supports up to 4K @ 30Hz video streams
- H.264/265 video codec, excellent for LAN and Internet transmission
- High image quality and ~80ms latency
- Supports seamless switching
- This unit is a Transceiver and can be used as a Transmitter, as a Receiver, or as both simultaneously
- Supports Video Wall
- Supports Multiview with up to 16-windows per screen
- RS232 for remote control of end devices
- PoE powered, via PoE (PSE) Ethernet Switch
- 2 Gang Wall-Plate
- Managed via Muximus Network Controller (500813)

Specification

Technical

Environment	HDMI 1.4
Devices	Blu-Ray, Set Top Boxes, projectors, monitors, TVs, PCs, supporting HDMI.
Signal Protocol/Standard	HDMI 1.4 and HDCP 1.4
Video Resolution	Up to 4K/30 in and out
Audio	3.5mm Line in/out, or HDMI audio
Latency	80 ~ 120ms
Network Bandwidth	Up to 12Mbps
Protocols	Supports Multicast, RTSP, RTMP
Compression	Supports H.264/265

Front Panel

Indicators	Power: Power indicator Sys: System indicator Link: LAN cable connection indicator HD: HDMI signal status
OLED Screen	Showing the Model, ID, IP, status

Rear Panel

Video	2 x HDMI Type-A
Control Ports	1 x RS232 phoenix connector 1 x Power phoenix connector
Audio	1 x 3.5mm IN 1 x 3.5mm OUT
LAN	1 x RJ45 (PoE)
USB	2 x USB-A ports for Keyboard & Mouse or PC host
Power	12VDC 1A

General

Control	<ul style="list-style-type: none">Muximus Network Controller3rd Party Control by TCP/ UDPWindows PC software, Android/iOS APP
Power Source	This device supports PoE (PD), an external power supply is not included. It is intended to be powered via a PoE (PSE) Ethernet Switch. If required, an optional power supply (500988) may be purchased separately.
Power Consumption	<10W
Temperature	Operating: 0° to 40°C Humidity: Up to 90% non-condensing
Dimensions	LxWxH (191mm x 100mm x 25mm)
Weight	1.2lbs (0.54kg)
Compliance	Regulatory: FCC, CE, RoHS
Warranty	2 years
Order Information	500865-WP-WH HDMI over IP PoE WP Seamless TRCV 4K30, White (UPC: 627699008652)
Accessories (These items are sold separately)	500988 Univ. PSU 12VDC/2.0A Lock US/UK/EU